

MODEL NUMBER (1)	CAPACITY GRAINS	(2)			(3)		(4)		SALT/REGEN. POUNDS	(5)	(6)		(7)		
		RESIN CU. FT.	MEDIA TANK DIA."	MEDIA TANK HT."	BRINE TANK DIA."	BRINE TANK HT."	SALT STORAGE POUNDS	CONT. FLOW GPM			PEAK FLOW GPM	BACKWASH FLOW GPM	FOOTPRINT W"	FOOTPRINT D"	FOOTPRINT H"
DCS-60-T-1S	60,000	2	12	52	18	40	450	30	16	21	3.5	42	18	61	
DCS-60-T-1.5S	60,000	2	12	52	18	40	450	30	27	40	3.5	42	18	62	
DCS-60-T-2S	60,000	2	12	52	18	40	450	30	32	50	3.5	42	18	64	
DCS-90-T-1S	90,000	3	14	65	18	40	450	45	17	22	5.0	44	18	74	
DCS-90-T-1.5S	90,000	3	14	65	18	40	450	45	31	43	5.0	44	18	75	
DCS-90-T-2S	90,000	3	14	65	18	40	450	45	39	53	5.0	44	18	77	
DCS-120-T-1S	120,000	4	16	65	24	40	700	60	18	23	6.3	54	24	74	
DCS-120-T-1.5S	120,000	4	16	65	24	40	700	60	35	45	6.3	54	24	75	
DCS-120-T-2S	120,000	4	16	65	24	40	700	60	48	65	6.3	54	24	77	
DCS-150-T-1S	150,000	5	18	65	24	40	700	75	20	25	8	56	24	74	
DCS-150-T-1.5S	150,000	5	18	65	24	40	700	75	42	57	8	56	24	75	
DCS-150-T-2S	150,000	5	18	65	24	40	700	75	68	85	8	56	24	77	
DCS-180-T-1S	180,000	6	18	65	24	54	900	90	19	24	8	56	24	74	
DCS-180-T-1.5S	180,000	6	18	65	24	54	900	90	41	54	8	56	24	75	
DCS-180-T-2S	180,000	6	18	65	24	54	900	90	64	81	8	56	24	77	
DCS-210-T-1S	210,000	7	21	62	24	54	900	105	18	23	11	59	24	71	
DCS-210-T-1.5S	210,000	7	21	62	24	54	900	105	39	52	11	59	24	72	
DCS-210-T-2S	210,000	7	21	62	24	54	900	105	61	78	11	59	24	74	
DCS-240-T-1.5S	240,000	8	24	72	24	54	900	120	43	57	14	62	24	82	
DCS-240-T-2S	240,000	8	24	72	24	54	900	120	75	97	14	62	24	84	
DCS-240-T-3S	240,000	8	24	72	24	54	900	120	120	171	14	62	24	86	
DCS-270-T-1.5S	270,000	9	24	72	24	54	900	135	42	55	14	62	24	82	
DCS-270-T-2S	270,000	9	24	72	24	54	900	135	70	94	14	62	24	84	
DCS-270-T-3S	270,000	9	24	72	24	54	900	135	118	161	14	62	24	86	
DCS-300-T-1.5S	300,000	10	24	72	24	54	900	150	40	55	14	62	24	82	
DCS-300-T-2S	300,000	10	24	72	24	54	900	150	69	92	14	62	24	84	
DCS-300-T-3S	300,000	10	24	72	24	54	900	150	114	151	14	62	24	86	
DCS-450-T-1.5S	450,000	15	30	72	30	48	1400	225	45	62	22	72	30	82	
DCS-450-T-2S	450,000	15	30	72	30	48	1400	225	85	106	22	72	30	84	
DCS-450-T-3S	450,000	15	30	72	30	48	1400	225	161	213	22	72	30	86	
DCS-600-T-2S	600,000	20	36	72	39	48	2200	300	87	110	32	87	39	84	
DCS-600-T-3S	600,000	20	36	72	39	48	2200	300	185	251	32	87	39	86	
DCS-750-T-2S	750,000	25	42	72	39	48	2200	375	105	136	43	93	42	84	
DCS-750-T-3S	750,000	25	42	72	39	48	2200	375	200	269	43	93	42	86	
DCS-900-T-2S	900,000	30	42	72	42	60	3100	450	115	146	43	96	42	84	
DCS-900-T-3S	900,000	30	42	72	42	60	3100	450	166	226	43	96	42	86	
DCS-1050-T-2S	1,050,000	35	48	72	42	60	3100	525	115	146	57	102	48	84	
DCS-1050-T-3S	1,050,000	35	48	72	42	60	3100	525	214	281	57	102	48	86	
DCS-1200-T-2S	1,200,000	40	48	72	42	60	3100	600	115	146	57	102	48	84	
DCS-1200-T-3S	1,200,000	40	48	72	42	60	3100	600	206	275	57	102	48	86	

NOTES:

- (1) SINGLE TIMER CONTROLLED SYSTEMS. METERS, TWIN, PROGRESSIVE FLOW & ALTERNATING TWIN UNITS AVAILABLE. -1 UNITS 1" IN/OUT NORYL VALVES. -1.5, -2, -3 BRASS NO LEAD VALVES
- (2) ALL RESIN VIRGIN 8% DVB IN SODIUM FORM
- (3) POLYETHYLENE INNER WRAPPED WITH EPOXY & MONO FILAMENT GLASS FOR STRENGTH
- (4) SEAMLESS BLOW MOLDED OR ROTATIONALLY MOLDED POLYETHYLENE
- (5) FIELD ADJUSTABLE TO LOWER FOR SALT SAVINGS AT EXPENSE OF HIGHER WATER TO DRAIN
- (6) AT PRESSURE DROP OF 15 PSI
- (7) AT PRESSURE DROP OF 25 PSI

DIME WATER, INC.			
TITLE COMMERCIAL SOFTENER SPECIFICATIONS			
SIZE A	CAGE CODE	DWG. NO.	REV.